



L'huile des records du monde

# YACCO XAS3

## Monograde detergent lubricant

### APPLICATIONS

Mineral SAE40 detergent oil specifically additivated for Diesel engines (including supercharged), used in regular service conditions. May be used in gasoline engines under light service conditions.

Also adapted to the lubrication of gearboxes, torque converters and hydraulic systems when the manufacturer requires the use of SAE 40 engine oil.

Suitable to a wide range of application: agriculture, garden equipment, marine, transportation, public works...

### MAIN CHARACTERISTICS

		Units	XAS3 SAE 40
Density at 20°C		kg/m <sup>3</sup>	895
Kinematic viscosity at 40°C		mm <sup>2</sup> /s	150
Kinematic viscosity at 100°C		mm <sup>2</sup> /s	14,9
Viscosity index			99
Pour Point		° C	- 9
Flash point Cleveland O. C.		° C	250
T.B.N. (Total Base Number)		mgKOH/g	11,4

*The data given in this table are typical production values and cannot be considered as specifications.*

### PROPERTIES & ADVANTAGES

- Highly detergent and dispersant properties allow to keep the engine clean
- Increased anti-wear, anti-oxidant, anti-corrosion properties for an optimal protection of the engine or transmissions.
- Good anti-foam and anti-rust properties
- Excellent shear resistance provides increased stability of the viscosity in service

### SPECIFICATIONS

CF/SF

Caterpillar TO-2

Mercedes-Benz MB 228.0

