



L'huile des records du monde

VX 1000 LL - SAE 0W-40

100 % synthetic longlife oil for gasoline, Diesel and LPG engines

APPLICATIONS

100% synthetic long life lubricant for very high performance gasoline, Diesel and LPG engines. Meets or exceeds the requirements of main car manufacturers. Recommended for heavily strained direct injection, multivalve, turbo-charged-or-not gasoline engines, and Diesel engines without DPF. Can be used under the most severe operating conditions (motorways, dense city traffic, sport etc.).

Adapted to all vehicles fitted with a catalytic converter and/or using LPG.

MAIN PHYSICAL DATA

		Units	0W-40
Density at	20° C	kg/m ³	841
Kinematic viscosity at	40° C	mm ² /s	76.5
Kinematic viscosity at	100° C	mm ² /s	13.5
Viscosity index			181
Flash point Cleveland open cup		° C	224
Pour point		° C	- 48
Dynamic viscosity at	- 35° C	mPa.s	5800

The data given in this table are typical production values and cannot be considered as specifications

PROPERTIES & ADVANTAGES

- Advanced 100% synthetic lubricant with specific additives. Exceeds the performance of most of the SAE 5W-40 and SAE 0W40 engine oils available on the market
- Excellent thermal and oxidation stability, providing increased oil service life and optimal engine protection, even during extended oil change intervals.
- Excellent shear resistance for increased viscosity control
- Outstanding low temperature capabilities ensure easy start-ups and instant wear protection
- High detergent and dispersant properties keep the engine clean, even under the most extreme operating conditions

APPROVALS

API SN
 Mercedes MB-Approval 229.5
 Porsche A40

SPECIFICATIONS

ACEA A3/B4
 BMW Longlife-01
 FORD WWS-M2C937-A
 Renault RN0710/ RN0700
 VW 502.00 / 505.00

