



L'huile des records du monde

MVX 500 4T – SAE 10W-40

Semi synthetic oil for 4 stroke motorbike engines

USES

Perfect lubrication of the engine working under extreme and **severe conditions** and **anytime** in the year.

Lubricates also the integrated gearboxes for a better protection box/ gearing (JASO MA2).

Is convenient to many types of motorbikes (roadsters, city, customs, GT or competition).

Is in accordance with Honda requirements for motorbikes from 2004.

MAIN CHARACTERISTICS

		Units	SAE 10W-40
Density	20° C	kg/m ³	864
Kinematic viscosity	40° C	mm ² /s	95.5
Kinematic viscosity	100° C	mm ² /s	14.4
Viscosity Index			156
Pour Point		° C	-39
Flash Point Cleveland open cup		° C	>210
Dynamic viscosity	-25° C	mPa.s	5800

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES


- Grade SAE 10W40 improving cold starts
- Quick lubrication when starting the engine
- Good levels of detergency and dispersivity
- Well adapted friction properties allowing a very good working of gearing
- Excellent protection against wear
- Keeps on the initial engine performances because of a good protection against deposit formation
- Reduces the pollution emissions and fuel consumption

HOMOLOGATIONS

SPECIFICATIONS

JASO MA2

API SL



JASO T903-2006
PERFORMANCE IS GUARANTEED by
YACCO S.A.S.

