



# AERO AVX 500 2T

Semi-synthetic oil for 2-stroke  
ultralight aircraft engines

## USES

Semi-synthetic formula complies with light and ultralight aircraft engines requirements.

AERO AVX 500 2T is specifically adapted to lubricate 2-stroke engines equipped with fuel injection systems or carburettor(s), including those used under severe service conditions (training, banner towing, etc.).

### Specifications:

API TC+

Anti-smoke properties

## MAIN PHYSICAL DATA

		Methods	Units	Values
Density at	20°C	ASTM D4052	kg/m <sup>3</sup>	870
Kinematic viscosity at	40°C	ASTM D445	mm <sup>2</sup> /s	82
Kinematic viscosity at	100°C	ASTM D445	mm <sup>2</sup> /s	11.4
Viscosity index		ASTM D2270		129
Pour point		ASTM D97	°C	-30
Cleveland Open Cup Flash Point		ASTM D92	°C	114
Colour				Blue

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ Excellent anti-smoke performance.
- ▶ Blue colored.
- ▶ Enhanced protection against carbon deposits and ring gumming.
- ▶ Instant miscibility with fuel.
- ▶ Low pour point for use at very low temperatures.



 [facebook.com/yaccosas](https://facebook.com/yaccosas)

 [twitter.com/yaccosas](https://twitter.com/yaccosas)

 [youtube.com](https://youtube.com)

