



TRANSPRO 15 - SAE 15W-40

Mineral oil for diesel and gasoline engines

USES

Suitable for diesel engines, including lorries, construction & agricultural equipment, stationary engines, generators, marine engines,...
TRANSPRO 15 – SAE 15W-40 is also suitable for gasoline and diesel engines in mixed fleets of vehicles where the manufacturer recommends the use of **API CH-4/SL or ACEA A3/B4 SAE 15W-40 oil**.
Compatible with vehicles fitted with catalytic converters.

Do not use in vehicles equipped with a Diesel Particulate Filter (DPF) and/or SRC system using AdBlue technology fluid.

Specifications:

ACEA E3; API CH4/SL; ACEA A3/B4; Man M 3275; MB 228.3

MAIN PHYSICAL DATA

	Methods	Units	15W-40
Density at 20°C	ASTM D4052	kg/m ³	872
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	101
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14
Viscosity index	ASTM D2270		141
Pour point	ASTM D97	°C	-36
Cleveland Open Cup Flash Point	ASTM D92	°C	212
Dynamic viscosity at -20°C	ASTM D5293	mPa·s	6200
HTHS viscosity	CEC L-036-90	mPa·s	3.8
Sulphated ash	ASTM D874	% mass	1.4
Total Base Number (TBN)	ASTM D2896	mgKOH/g	11

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Increased protection against wear and corrosion.
- ▶ Excellent dispersant-detergent properties for a clean engine.
- ▶ Specific additives allow the use in a wide range of vehicles and equipment (mixed-fleet)
- ▶ Multigrade SAE 15W-40 all-season engine oil.
- ▶ Excellent resistance to oxidation.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

