



Liquide Hydraulique Mineral CLEAN

LHM system cleaning fluid

USES

Recommended in the event of gumming or pollution in hydraulic systems which use green Mineral Hydraulic Fluid.

Liquide Hydraulique Minéral CLEAN **must never be used** in synthetic brake fluid compartments.

MAIN PHYSICAL DATA

		Methods	Units	Values
Density at	20°C	ASTM D4052	kg/m ³	855
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	18.5
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	5.0
Viscosity index		ASTM D2270		220

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ Detergent formula cleans and removes deposits in the hydraulic systems.
- ▶ Non-aggressive to seals.
- ▶ Compatible with LHM fluid.

INSTRUCTIONS FOR USE

1. Drain the hydraulic system as thoroughly as possible.
2. Fill with Liquide Hydraulique Minéral Clean and drive for 1500 km to 5000 km maximum.
3. Drain and fill with Liquide Hydraulique Minéral (LHM)



 facebook.com/yaccosas

 twitter.com/yaccosas

 youtube.com

