



# MVX QUAD 4 SYNTH - SAE 5W-40

100% synthetic oil for 4-stroke quad engines

## USES

Particularly recommended for 4-stroke quads with the latest engine technology used under the most severe driving conditions, all year round.

Also suitable for integrated gearboxes, MVX QUAD SYNTH 5W40 provides enhanced protection for gearbox/clutch assemblies (JASO MA2).

Suitable for all kinds of use (sports, professional, leisure). Exceeds the requirements of leading quad manufacturers.

## Specifications:

API SL

JASO T903:2011 MA2 oil code M033YCO200

## MAIN PHYSICAL DATA

		Methods	Units	5W-40
Density at	20°C	ASTM D4052	kg/m <sup>3</sup>	855
Kinematic viscosity at	40°C	ASTM D445	mm <sup>2</sup> /s	92
Kinematic viscosity at	100°C	ASTM D445	mm <sup>2</sup> /s	15.2
Viscosity index		ASTM D2270		175
Pour point		ASTM D97	°C	-39
Cleveland Open Cup Flash Point		ASTM D92	°C	226
Dynamic viscosity	-30°C	ASTM D5293	mPa·s	6200
HTHS viscosity (150°C)		CEC L-036-90	mPa·s	4.2
Sulphated ash		ASTM D874	% mass	0.9
Total Base Number (TBN)		ASTM D2896	mgKOH/g	7

The data given in this table represents typical production values and should not be taken as specifications.

## PROPERTIES & ADVANTAGES

- ▶ SAE 5W40 viscosity means quick oil flow upon start-up and optimal oil viscosity at very high temperatures.
- ▶ High shear-resistant viscosity index improves ensure viscosity is maintained in service and provide increased protection for engine and gearbox components.
- ▶ Excellent detergent/dispersant properties for a cleaner engine.
- ▶ 100% synthetic Ester-based formula reduces oil consumption.
- ▶ High friction coefficient as per JASO MA2 standard prevents slipping clutches.



**M033YCO200**  
**MA2**

JASO T903:2011

PERFORMANCE IS  
GUARANTEED by  
YACCO S.A.S.



[facebook.com/yaccosas](https://facebook.com/yaccosas)

[twitter.com/yaccosas](https://twitter.com/yaccosas)

[youtube.com](https://youtube.com)

