



SVX 1000 SNOW 4T - SAE 5W-40

100% synthetic oil for 4-stroke snowmobile engines

USES

100% synthetic oil specifically developed for use in modern 4-stroke snowmobile engines.

Outstanding engine protection under extreme driving conditions: professional or recreational use, racing, etc., ensuring safe operation of wet clutches.

Suitable for all kinds of gasoline and perfectly compatible with catalytic converters.

Specifications:

API SL
JASO MA2

MAIN PHYSICAL DATA

		Methods	Units	5W-40
Density at	20°C	ASTM D4052	kg/m ³	858
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	90
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	15
Viscosity index		ASTM D2270		176
Pour point		ASTM D97	°C	-39
Cleveland Open Cup Flash Point		ASTM D92	°C	225
Dynamic viscosity at	-30°C	ASTM D5293	mPa·s	6100

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ SAE 5W-40 oil grade provides excellent stability at high temperatures and instant lubrication upon start-up.
- ▶ 100% synthetic formula offers optimal protection at high temperatures and reduces oil consumption.
- ▶ Meets JASO MA2 clutch friction test requirements.
- ▶ Use of specific viscosity index improves to provide exceptional shear stability. This maintains viscosity in service and enhances the protection of the engine's parts.
- ▶ Good detergent/dispersant properties keep engines clean.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

