

YAHYPO C 80W90

High-quality mineral oil for rear axles of scooters

USES

For rear axles of scooters, where the manufacturer specifies the use of SAE 80W-90 oil.

Especially designed to meet the latest requirements of manufacturers. YAHYPO C 80W90 comes in a tube for ease of use.



API GL5 MIL-L-2105D

YAHYPO C SAE 80W90 meets the requirements of the leading manufacturers and far exceeds the performance levels above.



	Methods	Units	80W-90
Density at 20°C	ASTM D4052	kg/m³	880
Kinematic viscosity at 40°C	ASTM D445	mm²/s	157
Kinematic viscosity at 100°C	ASTM D445	mm²/s	15.5
Viscosity index	ASTM D2270		100
Pour point	ASTM D97	°C	-27
Cleveland Open Cup Flash Point	ASTM D92	°C	220
Brookfield viscosity at -26°C	ASTM D2983	mPa.s	140 000

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ► Grade SAE 80W90 provides excellent lubrication over a wide range of temperatures.
- ► Specific additives for increased resistance to oxidation and antiwear protection.
- ► Excellent anti-foam properties for constant protection against corrosion.
- ▶ Outstanding thermal stability and shear resistance. Viscosity maintained throughout the service life of the oil.
- ▶ Provides easier gear shifting and optimal protection of drive axles.











