



LUBE F – SAE 5W-30

100% synthetic fuel economy engine oil

USES

Specifically developed to meet the Ford WSS-M2C913-D & ST JLR.03.5003 specifications. LUBE F SAE 5W30 is suitable for most FORD & Jaguar Land Rover diesel /gasoline engines*.

This oil is also recommended when the manufacturer recommends these FORD/JLR specifications or the use of ACEA A5/B5, API SL/CF oil (Honda, Kia, Mazda, Toyota, Volvo, etc.).

Specifications:

ACEA A5/B5, API SL/CF, VWC 530 36

Ford WSS-M2C913-D acknowledgement

ST JLR.03.5003 Jaguar Land Rover acknowledgement

MAIN PHYSICAL DATA

		Methods	Units	5W30
Density at	20°C	ASTM D4052	kg/m ³	851
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	52
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	9.7
Viscosity index		ASTM D2270		174
Pour point		ASTM D97	°C	-48
Cleveland Open Cup Flash Point		ASTM D92	°C	212
Dynamic viscosity at	-30°C	ASTM D5293	mPa·s	4100
HTHS viscosity		CEC L-036-90	mPa·s	2,9
Sulphated ash		ASTM D874	% mass	1,15
Total Base Number (TBN)		ASTM D2896	mgKOH/g	10.2

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- Significant reduction in fuel consumption, thus lowering CO₂ and exhaust emissions, for a more environmentally-friendly oil.
- Outstanding protection against wear, especially for the parts of the engine's distribution.
- Fully compatible with the former specifications WSS-M2C913-C/913-B/913-A.
- Good resistance to shearing and high temperatures.
- Excellent oil flow at low temperatures (tested at -35°C).
- Very good anti-oxidation properties maintain optimal viscosity over the service life of the oil, including in engines running on biodiesel.

* Check the Ford or JLR recommended specification before use



facebook.com/yaccosas



twitter.com/yaccosas



youtube.com

